


<p>INDUSTRY CLEANSER TP GL SPECIAL</p>	<p>Item no.: 70 20 00</p>
<p>Areas of application</p>	<p>Industry Cleanser TP GL Special is a strong alkaline concentrate, especially developed for the removal of rubber from industry floors.</p> <p>Industry Cleanser TP GL Special is based on special detergents to remove strong oil residues and rubber caused by wheels of forklift trucks and other transportation equipment.</p> <p>Industry Cleanser TP GL Special is especially developed for the cleaning of industry tiles and floors coated by Epoxy Resin.</p>
<p>Method of application</p>	<p>Manual cleaning or using a spray system!</p> <p>Depending on the thickness of the residues use following concentration:</p> <p>Concentration: 5.0 – 10.0 % Temperature: cold – 40° C Time: 15 – 30 minutes</p> <p>After having used the product rinse thoroughly with drinking water to remove any possible residues!</p>
<p>Material compatibility</p>	<p>PVDF, PP, PE, PVC, Stainless Steel, Glass, Steel, Cast Iron</p> <p>Industry Cleanser TP GL Special must not be used on aluminium.</p> <p>In addition, further material incompatibilities cannot be excluded. Therefore, test the product on an unimportant spot before its definite use.</p>

Analysis of concentration	see titration method		
Physical and chemical properties			
Aspect/colour	Blue		
Form	Liquid		
Odour	Characteristic		
Foaming behaviour (see under conditions of application)	Slightly foaming		
Phosphates	Yes		
Density (20°C) g/cm³	1.105 – 1.125		
Concentration	1% in H₂O dest.	3% in H₂O dest.	5% in H₂O dest.
pH value (1%, 20°C)	12.0 – 12.6	not applicable	not applicable
Conductance (1%, 20°C) mS/cm	4.9 – 5.6	14.0 – 16.0	23.0 – 26.0
Phenolphthalein alkalinity (ml)	6.8 ± 0.5 (1 % at 30 ml sample)		
m-Value (ml)	not applicable		
Storage stability	+ 5° C – + 40° C		
Remarks regarding biocides	Not applicable		
Hazardous products and risk symbols	Caustic Soda Solution  DANGER		
Special remarks	Always close the container with the original closure, and store the items in a cool area without solar radiation. Product which was taken out of the container must never be poured back into the container. Read in any case our safety data sheet before using the product!		
Disposal	Disposal acc. to official regulations, in case of doubt contact the manufacturer.		

Please refer to our safety data sheets and our operating instructions with regard to precautionary measures, first aid measures and storage. The information given in the Sheet corresponds to the present state of our technical knowledge and experience. They do not constitute any guarantee; they are to be considered as basic information only. In particular they do not guarantee particular properties or the suitability for a concrete purpose. Because of the multitude of possible influences during the application of our products, the user has to make in any case the relevant tests and take the corresponding precautions. Any existing intellectual property rights are to be observed.