


Product properties – Technical sheet

VR X 74 S DEGREASER	Item no.: 00 13 07
Areas of application	<p>CONCENTRATED FOAM-CONTROLLED CLEANER AND DEGREASER TO BE USED IN AQUEOUS SPRAY-, FLOODING- AND IMMERSION-CLEANING PROCESSES.</p> <p>VR X 74 S is used in aqueous cleaning systems to clean, degrease, de-oil and de-wax parts coming from production or repair workshops.</p> <p>VR X 74 S is of particular use when a wide range of parts has to be cleaned.</p> <p>VR X 74 S supports the floating of oils and greases thus increasing the efficiency of oil skimmers.</p> <p>VR X 74 S is particularly suitable for the removal of drawing oils, drawing soap, residues of mould release agents, polishing pastes, lapping pastes and fluxing agents.</p> <p>VR X 74 S is of particular use for the cleaning of soldering frames because it allows removing even the dark spots on the aluminium working surfaces.</p> <p>Good biological degradability. Good separation of the dirt particles during waste water treatment.</p>
Corrosion protection	<p>VR X 74 S hasn't any components for corrosion protection to prevent sensitive material from corrosion.</p>
Method of application	<p>Suitable for automatic metering (time relay, volumetric control or control by conductance):</p> <p>Concentration: 0.5 – 3.0 % Temperature: 50 – 85°C Spray pressure: 2 – 6 bar Time: 1 – 3 minutes</p> <p>According to the desired quality standard the cleaned parts must be rinsed thoroughly with water or demineralised water to remove any possible residues!</p> <p>If parts are sensitive to corrosion an addition of a corrosion inhibitor into the last rinsing bath is necessary.</p>
Material compatibility	<p>PVDF, PP, PE, PVC, stainless steel, steel, grey cast iron, ceramic, glass, copper and aluminium.</p> <p>VR X 74 S must not be used on tin-plated material.</p> <p>In addition, further material incompatibilities cannot be excluded. Therefore, test the product on an unimportant spot before its definite use.</p>

Product properties – Technical sheet

Analysis of concentration	according to the titration instructions		
Physical and chemical properties			
Aspect/colour	Clear	Tawny – Brownish	
Form	Liquid		
Odour	Characteristic		
Foaming behaviour <small>(see under conditions of application)</small>	Not Foaming		
Phosphates	Contained		
Density (20°C) g/cm³	1.130 – 1.150		
Concentration	1 % in H₂O dest.	3 % in H₂O dest.	5 % in H₂O dest.
pH value (1 %, 20°C)	11.4 – 12.0	n/a	n/a
Conductance (1 %, 20°C) mS/cm	1.75 – 2.15	4.9 – 5.5	8.0 – 8.8
Phenolphthalein alkalinity (ml)	4.5 ± 0.5 (1 % at 50 ml sample)		
m-Value (ml)	n/a		
Storage stability	+ 5°C to + 40°C		
Remarks regarding biocides	n/a		
Hazardous products	Disodium metasilicate, pentahydrate		
Risk symbols			
	DANGER		
Special remarks	<p>Always close the container with the original closure, and store the items in a cool area without solar radiation. Product which was taken out of the container must never be poured back into the container.</p> <p>Read in any case our safety data sheet before using the product!</p>		
Disposal	Disposal acc. to official regulations, in case of doubt contact the manufacturer.		

Please refer to our safety data sheets and our operating instructions with regard to precautionary measures, first aid measures and storage. The information given in the Sheet corresponds to the present state of our technical knowledge and experience. They do not constitute any guarantee; they are to be considered as basic information only. In particular they do not guarantee particular properties or the suitability for a concrete purpose. Because of the multitude of possible influences during the application of our products, the user has to make in any case the relevant tests and take the corresponding precautions. Any existing intellectual property rights are to be observed.