

Product properties – Technical sheet

<p>LUBRICANT SD C</p>	<p>Item no.: 41 40 12</p>
<p>Areas of application</p>	<p>Lubricant SD C is a high concentrated agent with excellent lubricating effect to be used in centralized lubrication systems of conveying belts for bottles, cans and boxes in beverage and food industry.</p> <p>Lubricant SD C is especially developed for the use on PET – bottles. The approval of Coca Cola International is confirmed!</p> <p>Lubricant SD C avoids a clog up of pipes, valves, nozzles and sieves in the centralized lubrication system.</p> <p>Lubricant SD C is based on special cleansing components which allow hygienic surfaces on the conveying belts.</p> <p>Lubricant SD C works independent from the water hardness of the used water.</p>
<p>Method of application</p>	<p>Concentration: 0.1 – 0.2 % Temperature: cold – 30°C Time: permanent Application: Suitable for automatic metering, time relay or volumetric control</p> <p>It is advisable to have a periodical cleaning and maintenance of the dosing system, the pipes nozzles and sieves.</p>
<p>Material compatibility</p>	<p>PVDF, PP, PE, PVC, Stainless Steel, Glass</p> <p>Lubricant SD C must not be used on steel and cast iron. In addition, further material incompatibilities cannot be excluded. Therefore, test the product on an unimportant spot before its definite use.</p>

Product properties – Technical sheet

Analysis of concentration	according to the titration instructions		
Physical and chemical properties			
Aspect/colour	Clear	Dark Yellow – Brownish	
Form	Liquid		
Odour	Characteristic		
Foaming behaviour <small>(see under conditions of application)</small>	Slightly foaming		
Phosphates	n/a		
Density (20°C) g/cm³	0.995 – 1.015		
Concentration	1 % in H₂O dest.	3 % in H₂O dest.	5 % in H₂O dest.
pH value (1 %, 20°C)	5.0 – 7.0	n/a	n/a
Conductance (1 %, 20°C) mS/cm	n/a	n/a	n/a
Phenolphthalein alkalinity (ml)	n/a		
m-Value (ml)	n/a		
Storage stability	+ 5°C to + 30°C		
Remarks regarding biocides	n/a		
Hazardous products	Fatty alkylamine / acetic acid		
Risk symbols			
	DANGER		
Special remarks	<p>Always close the container with the original closure, and store the items in a cool area without solar radiation. Product which was taken out of the container must never be poured back into the container.</p> <p>Read in any case our safety data sheet before using the product!</p>		
Disposal	Disposal acc. to official regulations, in case of doubt contact the manufacturer.		

Please refer to our safety data sheets and our operating instructions with regard to precautionary measures, first aid measures and storage. The information given in the Sheet corresponds to the present state of our technical knowledge and experience. They do not constitute any guarantee; they are to be considered as basic information only. In particular they do not guarantee particular properties or the suitability for a concrete purpose. Because of the multitude of possible influences during the application of our products, the user has to make in any case the relevant tests and take the corresponding precautions. Any existing intellectual property rights are to be observed.