Product properties – Technical sheet



FE HD LIQUID PHOSPHATISING AGENT

Item no.:

00 07 69

Areas of application

FE HD LIQUID is used in washing and phosphatising units to clean and phosphatise steel and cast iron parts etc. in immersion cleaning equipment or high pressure cleaning.

FE HD LIQUID produces on iron, steel and cast iron tight, iridescent yellowish to greenish-blue iron phosphate layers. The resulting iron phosphate acts as a temporary rust protection and in particular as a pre-treatment for a better adhesion of aqueous paints, usual paints containing solvents and powder paints. Also for aluminium, zinc and brass parts cleaned with this method the adhesion of the paints applied is better. Special components reduce the formation of sludge and deposits on the parts cleaned when the machine is stopped. Dry residues can be rinsed off easily.

Method of application

Rinsing liquors:

Rinse the phosphatised parts thoroughly with sufficient clear water to completely remove any phosphate in excess and water salts.

To passivate the parts add Rinsing Agent FE,

Art.-No. 000712, to the rinsing liquor before last. A last rinsing with demineralised water to remove water salts improves the adhesion of paints. Allow the parts to dry by their natural heat or place them into a drying cabinet.

Concentration: 1.5 – 3.0 % Temperature: 40 – 75°C Time: 1 – 3 minutes

According to the desired quality standard the cleaned parts must be rinsed thoroughly with water or demineralised water to remove any possible residues!

Material compatibility

PVDF, PP, PE, PVC, PTFE, PFA.

FE HD LIQUID changes surfaces of steel, aluminium and cast iron. The product is **not suitable** for polished surfaces; because of the pickling reaction the surfaces become rough.

In addition, further material incompatibilities cannot be excluded. Therefore, test the product on an unimportant spot before its definite use.

000769.docx 1

Status: 22nd November, 2019

Product properties – Technical sheet



Analysis of concentration	see titration method		
Physical and chemical properties			
Aspect/colour	Clear Colourless		
Form	Liquid		
Odour	Weak Characteristic		
Foaming behaviour (see under conditions of application)	Not Foaming		
Phosphates	Contained		
Density (20°C) g/cm³	1.165 – 1.185		
Concentration	1 % in H₂O dest.	3 % in H₂O dest.	5 % in H₂O dest.
pH value (1 %, 20°C)	2.4 - 3.0	not applicable	not applicable
Conductance (1 %, 20°C) mS/cm	1.8 – 2.2	4.15 – 4.85	6.3 – 7.3
Phenolphthalein alkalinity (ml)	6.5 ± 0.5 (1 % at 30 ml sample)		
m-Value (ml)	not applicable		
Storage stability	+ 5°C to + 30°C		
Remarks regarding biocides	not applicable		
Hazardous products	Orthophosphoric acid / 2-(2-butoxyethoxy)ethanol		
Risk symbols	<u>(!)</u>		
	WARNING		
Special remarks	Always close the container with the original closure, and store the items in a cool area without solar radiation. Product which was taken out of the container must never be poured back into the container. Read in any case our safety data sheet before using the product!		
Disposal	Disposal acc. to official regulations, in case of doubt contact the manufacturer.		

Please refer to our safety data sheets and our operating instructions with regard to precautionary measures, first aid measures and storage. The information given in the Sheet corresponds to the present state of our technical knowledge and experience. They do not constitute any guarantee; they are to be considered as basic information only. In particular they do not guarantee particular properties or the suitability for a concrete purpose. Because of the multitude of possible influences during the application of our products, the user has to make in any case the relevant tests and take the corresponding precautions. Any existing intellectual property rights are to be observed.

000769.docx 2