GRAFFITI REMOVER

Product properties – Technical sheet



Item	no.:

00 13 22

	00 13 22		
Areas of application			
	Graffiti Remover is a special concentrate to remove water- and oil based paints and felt pen marks from all surfaces (outside walls, surfaces made from glass, facades).		
	Graffiti Remover dissolves colour coats one by one without subjacent paint layers.		
	Graffiti Remover works at room temperature, the supply of heat is not necessary.		
	Graffiti Remover is a very mild product, and can be quickly neu- tralized with water. Besides sufficient ventilation no further pro- tective measures are necessary during use.		
	Graffiti Remover is free from chlorinated hydrocarbons.		
Method of application			
	Manual cleaning or with a spray system:		
	Concentration: undiluted Temperature: 10 – 30°C Time: 15 – 30 minutes		
	After having used the product rinse thoroughly with drinking water to remove any possible residues!		
Material compatibility			
	Stainless Steel, Steel, Cast Iron, Non Ferrous Metals, Glass Concrete		
	Graffiti Remover must not be used on plastic, especially per- spex. In addition, further material incompatibilities cannot be ex- cluded. Therefore, test the product on an unimportant spot be- fore its definite use.		

Product properties – Technical sheet



Analysis of concentration	n/a			
Physical and chemical	properties			
Aspect/colour	Clear Colourless			
Form	Liquid			
Odour	Characteristic			
Foaming behaviour (see under conditions of application)	Not foaming			
Phosphates	n/a			
Density (20°C) g/cm ³	1.070 – 1.090			
Concentration	1 % in H ₂ O dest.	3 % in H ₂ O dest.	5 % in H ₂ O dest.	
pH value (1 %, 20°C)	n/a	n/a	n/a	
Conductance (1 %, 20°C) mS/cm	n/a	n/a	n/a	
Phenolphthalein alkalinity (ml)	n/a			
m-Value (ml)	n/a			
Storage stability	- 5°C to + 30°C			
Remarks regarding biocides	n/a			
Product contains	Reaction mass of dimethyl adipate and dimethyl glutarate and di- methyl succinate			
Risk symbols	THE PRODUCT IS NOT CLASSIFIED ACCORDING TO THE CLP REGULATION AND REQUIRES NO LABELING!			
Special remarks	Always close the container with the original closure, and store the items in a cool area without solar radiation. Product which was taken out of the container must never be poured back into the container. Read in any case our safety data sheet before using the product!			
Disposal	Disposal acc. to official regulations, in case of doubt contact the manufacturer.			

Please refer to our safety data sheets and our operating instructions with regard to precautionary measures, first aid measures and storage. The information given in the Sheet corresponds to the present state of our technical knowledge and experience. They do not constitute any guarantee; they are to be considered as basic information only. In particular they do not guarantee particular properties or the suitability for a concrete purpose. Because of the multitude of possible influences during the application of our products, the user has to make in any case the relevant tests and take the corresponding precautions. Any existing intellectual property rights are to be observed.