Product properties – Technical sheet



| POWER GEL | | Item no.: | |
|------------------------|---|-----------------------------|--|
| ALK | | 00 14 20 | |
| Areas of application | | | |
| | Power Gel ALK is a highly efficient concentrated cleanser to be used in foam generators and devices. | | |
| | Power Gel ALK has a special detergent to build between the surfaces and the foam a thin film like gel in order to increase the soaking time. | | |
| | Power Gel ALK is particularly suitable for the quick cleansing of big surfaces in the food and beverage industry. | | |
| | Power Gel ALK easily removes organic residues, grease and other general residues on tables, floors and walls. | | |
| Mathed of employers | | | |
| Method of application | | | |
| | Cleaning with a foam spray system! | | |
| | Depending on the desired foam consistency use following concentration: | | |
| | Concentration: 2.0 – 10.0 % Temperature: 5 – 80°C Time: 10 – 20 minutes | | |
| | After having used the product rinse thoroughly with drinking water to remove any possible residues! | | |
| | | | |
| Material compatibility | | | |
| | | | |
| | PVDF, PP, PE, PVC, Stainless Stee | el, Steel, Cast Iron, Glass | |
| | Power Gel Acid must not be used on aluminium. | | |
| | In addition, further material incompatibilities cannot be excluded. Therefore, test the product on an unimportant spot before its definite use. | | |

001420.docx 1

Status: 21st February, 2023

Product properties – Technical sheet



| Analysis of concentration | according to the titration instructions | | | |
|---|---|------------------|------------------|--|
| Physical and chemical properties | | | | |
| Aspect/colour | Clear Slightly Brownish – Brownish | | | |
| Form | Liquid | | | |
| Odour | Alcohol-like | | | |
| Foaming behaviour (see under conditions of application) | Strong Foaming | | | |
| Phosphates | n/a | | | |
| Density (20°C) g/cm³ | 1.100 – 1.120 | | | |
| Concentration | 1 % in H₂O dest. | 3 % in H₂O dest. | 5 % in H₂O dest. | |
| pH value (1 %, 20°C) | 12.1 – 12.7 | n/a | n/a | |
| Conductance (1 %, 20°C) mS/cm | 4.3 – 5.3 | 12.0 – 15.0 | 19.5 – 24.5 | |
| Phenolphthalein alkalinity (ml) | 6.5 ± 1.0 (1 % at 30 ml sample) | | | |
| m-Value (ml) | n/a | | | |
| Storage stability | + 5°C to + 40°C | | | |
| Remarks regarding biocides | n/a | | | |
| Hazardous products | Sodium Hydroxide / Amines, C12-14 (even numbered) alkyldimethyl, N-oxides | | | |
| Risk symbols | | | | |
| | DANGER | | | |
| Special remarks | Always close the container with the original closure, and store the items in a cool area without solar radiation. Product which was taken out of the container must never be poured back into the container. Read in any case our safety data sheet before using the product! | | | |
| Disposal | Disposal acc. to official regulations, in case of doubt contact the manufacturer. | | | |

Please refer to our safety data sheets and our operating instructions with regard to precautionary measures, first aid measures and storage. The information given in the Sheet corresponds to the present state of our technical knowledge and experience. They do not constitute any guarantee; they are to be considered as basic information only. In particular they do not guarantee particular properties or the suitability for a concrete purpose. Because of the multitude of possible influences during the application of our products, the user has to make in any case the relevant tests and take the corresponding precautions. Any existing intellectual property rights are to be observed.

001420.docx 2