#### **Product properties – Technical sheet**



# LUBRICANT SK 41 40 16

#### **Areas of application**

**Triple Concentrate** with excellent lubricating effect to be used in centralized lubrication systems of conveying belts for bottles, cans and boxes in beverage and food industry.

**Lubricant SK** avoids a clog up of pipes, valves, nozzles and sieves in the centralized lubrication system.

**Lubricant SK** is based on special cleansing components which allow hygienic surfaces on the conveying belts.

**Lubricant SK** works independent from the water hardness of the used water.

#### **Method of application**

Concentration: 0.025 – 0.05 % Temperature: 10 – 30° C

**Time**: permanent

Application: Suitable for automatic metering (time relay or volu-

metric control).

It is advisable to have a periodical cleaning and maintenance of the dosing system, the pipes nozzles and sieves.

### **Material compatibility**

PVDF, PP, PE, PVC, Stainless Steel, Glass

**Lubricant SK** must not be used on steel and cast iron. In addition, further material incompatibilities cannot be excluded. Therefore, test the product on an unimportant spot before its definite use.

414016.docx 1

Status: 03rd November 2017

## **Product properties – Technical sheet**



Analysis of concentration	see titration method		
Physical and chemical properties			
Aspect/colour	Yellow-Brown		
Form	Liquid		
Odour	Characteristic		
Foaming behaviour (see under conditions of application)	Slightly foaming		
Phosphates	not applicable		
Density (20°C) g/cm³	1.030 – 1.050		
Concentration	1 % in H <sub>2</sub> O dest.	3 % in H <sub>2</sub> O dest.	5 % in H <sub>2</sub> O dest.
pH value (1 %, 20°C)	4.5 – 6.5	not applicable	not applicable
Conductance (1 %, 20°C) mS/cm	not applicable	not applicable	not applicable
Phenolphthalein alkalinity (ml)	not applicable		
m-Value (ml)	not applicable		
Storage stability	+ 5°C to + 30°C		
Remarks regarding biocides	not applicable		
Hazardous products	Fatty alkyl amine / acetic acid		
Risk symbols		DANGER	
	DANGEN		
Special remarks	Always close the container with the original closure, and store the items in a cool area without solar radiation.  Product which was taken out of the container must never be poured back into the container.  Read in any case our safety data sheet before using the product!		
Disposal	Disposal acc. to official regulations, in case of doubt contact the manufacturer.		

Please refer to our safety data sheets and our operating instructions with regard to precautionary measures, first aid measures and storage. The information given in the Sheet corresponds to the present state of our technical knowledge and experience. They do not constitute any guarantee; they are to be considered as basic information only. In particular they do not guarantee particular properties or the suitability for a concrete purpose. Because of the multitude of possible influences during the application of our products, the user has to make in any case the relevant tests and take the corresponding precautions. Any existing intellectual property rights are to be observed.

414016.docx 2